

Product Specifications: Hardware

Part	Material	Thickness (inches)
Module side and back panels	ASTM A1008 CS Type B Steel, Powder Coat Finish	18 GA (.048) Thickness
Module Doors	ASTM A1008 CS Type B Steel, Powder Coat Finish	16 GA (.060) Thickness
	ASTM A1008 CS Type B Steel, Powder Coat Finish	14 GA (.075) Thickness
Module Door Latch Point	18-8 Stainless Steel Rod, Mill Finish	.19 Diameter
Module Latch	304 Stainless Steel, 2B Finish	.12 Thickness
Module Shelf	5052-H32 Aluminum, Mill Finish	.05 Thickness
Module Crossbar / Shelf Support	Extruded 6063-T6 Aluminum, Clear Anodize Finish	0.60 X 0.60 U-Shape Cross Section
Module Master Manual Access Release	304 Stainless Steel, 2B Finish	.05 Thickness
Module Master Access Latching Cam	304 Stainless Steel, 2B Finish	.12 Thickness
Module Assembly Top	ASTM A1008 CS Type B Steel, Powder Coat Finish	18 GA (.048) Thickness
Module Assembly Joiners and Finish Panels	ASTM A1008 CS Type B Steel, Powder Coat Finish	18 GA (.048) Thickness
Module Base	ASTM A1008 CS Type B Steel, Powder Coat Finish	14 GA (.075) Thickness
	ASTM A36 Mild Steel, Powder Coat Finish	.19 Thickness

LEED Information

Materials and Resources Credit 5: Regional Materials	Products used within 500 miles of Manhattan, KS may contribute to this credit.
Materials and Resources Credit 4: Recycled Content	Our product contains 20% pre- and 30% post- consumer recycled content. Thus, 40% of the total dollars spent on our products may contribute to the Recycled Content Credit.

Testing & Safety

Door & Switch Testing	Tested for 100,000+ cycles
-----------------------	----------------------------



The Package Concierge locker system, manufactured by Florence Corporation, complies with the Standards and requirements of UL-2361 and is identified with the ETL Listed Mark. (ETL Certification #: 4010527)

